

Performance Data:

Model: FL-L

Air Flow Rate (L/s/m)	Nominal Duct Height or Weight (mm)	Pressure (Pa)	Velocity (m/s)	Throw (m)	Noise NC (dB)
40	50	3	1.25	1.1 - 1.2	–
50	50	4	1.50	1.7 - 3.1	15
60	50	8	2.00	2.3 - 4.3	15
75	50	12	2.50	2.9 - 5.2	23
	75	4	1.40	2.5 - 4.0	–
90	50	15	3.00	3.3 - 6.0	25
	75	5	1.65	2.7 - 4.6	18
	100	2	1.15	2.1 - 3.7	14
110	50	20	3.50	4.0 - 6.9	27
	75	8	2.00	3.2 - 5.6	19
	100	4	1.35	2.6 - 4.6	15
125	50	20	3.50	4.0 - 6.9	27
	75	8	2.00	3.2 - 5.6	19
	100	4	1.35	2.6 - 4.6	15
140	75	12	2.50	3.6 - 7.1	25
	100	6	1.75	3.1 - 5.8	20
	125	4	1.30	2.7 - 4.8	16
160	75	14	2.80	4.7 - 8.0	28
	100	6	1.90	3.6 - 6.6	22
	125	4	1.50	3.1 - 5.6	19
190	75	20	3.50	5.5 - 8.6	31
	100	10	2.40	4.5 - 7.5	24
	125	6	1.80	3.6 - 6.5	21
	150	4	1.50	3.4 - 5.7	15
230	75	28	4.20	6.7 - 11	35
	100	15	3.00	5.9 - 9.2	26
	125	9	2.20	5.4 - 7.8	23
	150	6	1.80	4.8 - 7.0	17
270	100	20	3.35	6.8 - 10	28
	125	12	2.50	6.3 - 8.8	25
	150	8	2.00	5.6 - 8.1	20
	200	4	1.50	4.8 - 7.2	14
310	100	22	3.80	8.2 - 13	32
	125	15	3.00	6.8 - 12	28
	150	10	2.35	6.1 - 10.2	24
	200	5	1.70	5.3 - 9.1	18
350	125	19	3.30	7.3 - 11.2	32
	150	13	2.65	6.4 - 10.3	27
	200	6	1.90	5.7 - 9.1	21
	250	4	1.50	4.2 - 7.8	18
390	125	22	3.65	7.9 - 11.5	37
	150	15	2.95	7.5 - 10.8	29
	200	8	2.10	6.5 - 10.2	25
	250	5	1.65	5.9 - 9.0	21
430	150	19	3.25	8.0 - 11.2	33
	200	10	2.35	7.3 - 11	28
	250	6	1.85	6.2 - 9.8	25
	300	4	1.50	5.7 - 8.6	19
470	150	20	3.50	9.2 - 12	38
	200	12	2.50	8.0 - 11.2	33
	250	8	2.00	7.1 - 10.3	28
	300	5	1.65	6.3 - 9.1	21
540	200	15	3.00	9.5 - 14.5	38
	250	10	2.30	8.7 - 12.5	32
	300	6	1.90	7.3 - 11.2	24