

**Performance Data:**

Air flow rate (l/s)	Cross Talk Attenuator Models													
	CTA-U1 / CTA-Z1		CTA-U2 / CTA-Z2 / CTA-L1		CTA-U3 / CTA-Z3 / CTA-L2		CTA-U4 / CTA-Z4		CTA-U5 / CTA-Z5 / CTA-L3		CTA-L4		CTA-L5	
	Pa	NC	Pa	NC	Pa	NC	Pa	NC	Pa	NC	Pa	NC	Pa	NC
20	3	<20	-	-	-	-	-	-	-	-	-	-	-	-
30	5	25	3	<20	-	-	-	-	-	-	-	-	-	-
40	8	27	5	25	3	<20	-	-	-	-	-	-	-	-
50	13	28	8	26	5	24	3	<20	-	-	-	-	-	-
60	18	29	10	27	6	25	5	24	3	<20	-	-	-	-
70	23	31	13	28	8	26	7	25	4	<20	4	<20	-	-
80	30	32	17	29	10	27	9	26	5	24	5	24	-	-
90	38	33	21	30	14	28	10	27	6	25	6	25	-	-
100	44	34	26	32	17	29	13	28	8	26	7	26	4	24
120	60	36	32	33	20	30	16	29	12	27	9	27	6	25
140	75	38	42	34	27	32	20	30	15	28	12	28	8	26
160	95	40	54	36	33	33	26	32	20	29	15	29	10	27
180	-	-	72	37	43	34	33	33	26	30	20	30	13	28
200	-	-	93	40	55	36	43	34	32	31	25	31	15	29
220	-	-	-	-	68	37	48	35	36	32	29	32	17	30
240	-	-	-	-	78	38	58	36	42	33	32	33	20	31
260	-	-	-	-	89	40	70	37	50	34	38	34	24	31
280	-	-	-	-	-	-	80	38	60	35	42	35	28	32
300	-	-	-	-	-	-	90	40	70	36	50	36	32	33
320	-	-	-	-	-	-	-	-	78	37	59	37	36	34
340	-	-	-	-	-	-	-	-	90	38	68	38	41	35
360	-	-	-	-	-	-	-	-	100	40	77	39	45	36
380	-	-	-	-	-	-	-	-	-	-	84	40	50	37
400	-	-	-	-	-	-	-	-	-	-	70	42	58	38
420	-	-	-	-	-	-	-	-	-	-	-	-	64	39
440	-	-	-	-	-	-	-	-	-	-	-	-	70	40
460	-	-	-	-	-	-	-	-	-	-	-	-	76	42
480	-	-	-	-	-	-	-	-	-	-	-	-	85	43
500	-	-	-	-	-	-	-	-	-	-	-	-	92	45

**Insertion Loss Data, dB**

Attenuator length L in mm	Octave Centre Band Frequency in Hz							
	63	125	250	500	1000	2000	4000	8000
500	5	7	10	15	23	17	13	11
750	6	9	14	23	37	29	22	16
1000	8	11	19	31	48	37	28	21
1250	9	14	23	38	50	44	32	26
1500	10	16	27	45	50	50	39	31